



PB32

HEIGHT	WIDTH	DEPTH	TRAVEL	WEIGHT
300mm (11.7/8")	90mm (3.1/2")	240mm (9.1/2")	165mm (6.1/2")	12.5kgs

TOTAL POWER:	770 watt
MOTOR:	720 watt
MAGNETIC ADHESION:	1000kgs
VOLTAGE:	220/240v or 110v (A.C. Supply)
SPEED:	550 rpm (no load)
CUTTER CAPACITY:	12mm to 32mm
DRILLING CAPACITY:	18mm

MODEL NO	VOLTAGE
PB 32	240/110 VOLTS

The POWERBOR® PB32 has been ergonomically designed to provide an electromagnetic drilling machine that is totally user friendly.

- Fitted with the reliable and proven HITACHI D13 power unit
- Free 13mm drill chuck*
- A complete coolant system is available
- All Powerbor® standard features are backed by a full range of replacement spares

12 months comprehensive warranty as standard

* To fit drill chuck (13mm with 1/2" x 20) remove arbor (RH thread) and arbor support bracket.



PB32 COMBI

HEIGHT	WIDTH	DEPTH	TRAVEL	WEIGHT
300mm (11.7/8")	90mm (3.1/2")	240mm (9.1/2")	165mm (6.1/2")	12.5kgs

TOTAL POWER:	770 watt
MOTOR:	720 watt
MAGNETIC ADHESION:	1000kgs
VOLTAGE:	220/240v or 110v (A.C. Supply)
SPEED:	25-550 rpm variable (no load)
CUTTER CAPACITY:	12mm to 32mm
DRILLING CAPACITY:	18mm
TAPPING CAPACITY:	12mm

MODEL NO	VOLTAGE
PB 32 COMBI	240/110 VOLTS

The PB32 Combi has the same excellent power to weight ratio as the PB32. In addition it has forward, reverse and variable speed as standard providing a choice of tapping, cutting and drilling capability.

- Forward and reverse facility
- Fitted with the reliable and proven HITACHI D13 power unit
- Free 13mm drill chuck*
- A complete coolant system is available
- All Powerbor® standard features are backed by a full range of replacement spares

12 months comprehensive warranty as standard

* To fit drill chuck (13mm with 1/2" x 20) remove arbor (RH thread) and arbor support bracket.

THE POWERBOR® STANDARD - INCLUDED WITH ALL MACHINES

- Dual carrying handles for enhanced operating manoeuvrability
 - Reversible handles for use in restrictive conditions
 - Improved high density magnet for maximum adhesion
 - Corrosive resistant, tangle-free cable from stand to drill unit
- Isolating power relay for improved handling safety
- Control panel situated conveniently on the same side as the traverse handles
 - Free protective carrying case complete with safety strap, cutting fluid, safety guard and folding hex key set