

## HYDRAULIC CUTTING TOOL


general features

OVERHEAD LINE APPLICATION  
**HT-TC051Y**

Max cutting Ø mm	Dimensions mm		Weight kg
	length	width	
50	503	129	4,7

### STORAGE

Type	Dimensions mm	Weight kg	Supplied with the tool	Available upon request
Canvas Bag 010	510x152	0,15	✳	—



Hand operated hydraulic tool specifically designed to cut copper, aluminum, aluminum-steel cables (ACSR) having a max overall diameter of 50 mm. The HT-TC051Y is provided with a two stage hydraulic system, which advances the blades quickly to the cable. This proven system saves operator time and effort. The HT-TC051Y is provided with an automatic safety valve to bypass oil when reaching max pressure. This means safety to the operator and protection to the blades. The blades are manufactured from high strength special steel, heat treated to ensure a long service life. The shape of the blades provides a "clean" cut. The head can be opened to allow cutting of running cables and ropes. The head rotates 90 degrees allowing the operator to perform the cut in the most comfortable position. The tool is supplied complete with canvas bag 010 for protection and storage when not in use.

**Does not cut stay wire, steel wire or earthing rod.**

## HYDRAULIC CUTTING HEAD

general features

OVERHEAD LINE APPLICATION  
**TC 050Y**



Max cutting Ø mm	Max operating pressure bar	Dimensions mm		Weight kg
		length	width	
50	700	331	112	3,3

### STORAGE

Type	Dimensions mm	Weight kg	Supplied with the tool	Available upon request
Canvas bag 011	360x137	0,13	✳	—



Hydraulic cutting head complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max, (see page 120). TC 050Y features the same cutting capability as HT-TC051Y.

**Does not cut stay wire, steel wire or earthing rod.**